



SHOTBLAST ENGRAVING MASK SYSTEMS

PrecisionMasks . Oatfield House . Campbeltown . Argyll . PA28 6PH . Scotland

Tel: +44 (0) 1586 551818 . Fax: +44 (0) 1586 551855

www.precisionmasks.com

PRECISIONMASKS™ EQUIPMENT SPECIFICATION

Washout Booth

FEATURES:

- Galvanised Construction
- Flow/Temperature control
- Back Illuminated Panel
- Pressure Pump
- Air Operated Light Switch

The PrecisionMask™ Processing Booth is of substantial, galvanised steel construction.

A brightly illuminated rear panel, vital to ensuring the complete processing of finer detailed resists, is controlled by an electrically safe, air operated switch.

The high pressure in-line pump supplies water to a hand held spray unit via a fully adjustable mixer valve



located inside the booth.

Confirmation of the water temperature is given by an in-line temperature gauge.

A low pressure cold water supply

is all that is normally required for this system to operate correctly. In colder winter temperatures, however, a hot water supply may also be necessary for efficient washing out.

Power requirements for the pump and lighting circuits are single phase.

SPECIFICATIONS:

Lit Panel- 56 x 71cm (22" x 28")
Width - 86cm (34")
Height - 168cm (66")
Depth - 84cm (33")
Weight - 86kg (190lbs)
Voltage - 220/240 Volts 50/60Hz
(alternative voltages can be supplied)
Current - 5 amperes (max)

Film Laminator

FEATURES:

- Single Phase
- Aluminium Bed
- Right or Left handed
- Heavy Duty Bench Clamps
- Quiet Power Unit

The PrecisionMask™ Hand Operated Film Laminator is a unique, purpose designed unit. Easy to use, it is quick and reliable in operation and efficiently produces a consistent product.

Based on an extra heavy duty steel frame, the PrecisionMask™ Film Laminator is fastened to the workbench by a pair of substantial hand clamps.



The main laminating bed is of internally stiffened aluminium with gas strut assisted action. Power is provided by a quiet, remotely mounted industrial vacuum pump.

A standard PrecisionMask™ sheet size hand laminator is

provided, together with a spare (additional and special size laminators can be supplied to order).

Any drips are taken care of by a welded stainless steel tray fitted to the base.

The unit is single phase and can be operated from a normal domestic electricity supply.

SPECIFICATIONS:

Width - 35cm (14")
Height - 54cm (22") max
Depth - 42cm (17") max
Weight - 20kg (44lbs) approx
Voltage - 220/240 Volts 50/60Hz
(alternative voltages can be supplied)
Current - 5 amperes

PrecisionMasks Limited

Registered in England Number: 2804670 Registered Office: 21 Orchard Gardens, Teignmouth, Devon TQ14 8DG